

AC/DC OPEN LOOP SPLIT CORE TRANSDUCER

Accurate, Rugged, Versatile and Reliable

- Two models AT 1000 and ATi 1000. **(TRUE RMS)**
- AC / DC up to 1000Amps.
- Instantaneous Voltage or 4 to 20mA Current Outputs (True RMS).
- Excellent Accuracy with High Resolution.
- Split Core for Non-Invasive Current Measurement.
- Compact Lightweight Design.
- Broad Bandwidth DC to 10kHz.
- DIN Rail and Panel Mount Options.

IP40



Safety and EMC Conformance

Conformance to European standards for safety and EMC ensures a safe product with high reliability through reduced susceptibility to electromagnetic interference.

Typical Applications

- Railway Trackside Applications.
- Battery Charging Systems.
- Automotive Applications.
- Power Supplies for Telecoms.
- Airport Lighting Circuits.

SPECIFICATIONS

NON-INVASIVE AC / DC SPLIT CORE CURRENT TRANSDUCERS		
MODEL	AT 1000	ATi 1000
Current Range	1000A DC or AC <i>PEAK</i>	1000A DC or AC <i>RMS</i>
Output Sensitivity	10mV/A w.r.t. 0V	4 to 20mA DC (True RMS)
Output Zero Drift	±5mV/°C	±500mA/°C Primary
Output Connection	Via 5 pin connector Phoenix MC1, 5/5-G-3, 81 or 2.9m screened cable	
Frequency Range	DC to 10kHz (-3dB)	
Resolution	± 100mA	
Basic Accuracy	± 1% of reading ± 0.5A	± 1% of range
Conductor Position Sensitivity	<± 1% relative to centre reading	
Conductor Diameter	25mm maximum	
Power Supply	± 15V ±10% external	+ 9V to +36V external
Current Consumption	20mA	35mA + I _{OUT}
Load Impedance	> 10 kOhms	≤ 300Ω

Environmental data

Operating Temperature: -20°C to 65°C (-4°F to 149°F)

Temp. Coefficient: ±0.02% of reading per °C

Storage Temperature: -20°C to 85°C (-4°F to 185°F)

All accuracies stated at: 23°C ± 1°C (73.4°F ± 1.8°F)

Ingress Protection: IP40 (Jaws closed)

Part / Model Number

P-16.600.0 AT 1000

P-16.600.1 ATi 1000

Also available with cable output:

P-16.600.2 AT 1000C

P-16.600.3 ATi 1000C

Safety

EN 61010-1, EN 61010-2-032
300V RMS Measurement Category III
Pollution Degree 2

300V AC RMS or DC between uninsulated conductor and ground

EN 61326-1 for equipment intended to be use in an industrial electromagnetic environment

Mechanical Data

Dimensions: (mm) 100(H) x 65(W) x 25(D)

Jaw Capacity: Ø 25mm

Weight: 120g

GMC-I PROSYS Ltd offers a wide range of non-invasive Probes, Clamp Meters and Transducers for the measurement and analysis of Current and Voltage.